

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 2 of 12

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves and eye/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
106-97-8	butane			40 - < 45 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane			20 - < 25 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-64-1	Acetone; Propan-2-one; Propanone			5 - < 10 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 3 of 12

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/vapour/aerosol.

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 4 of 12

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Pet care

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-64-1	Acetone; Propan-2-one; Propanone			
	Worker DNEL, long-term	inhalation	systemic	1210 mg/m ³
	Worker DNEL, acute	inhalation	local	2420 mg/m ³
	Worker DNEL, long-term	dermal	systemic	186 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	200 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	62 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	62 mg/kg bw/day
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	2035 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	608 mg/m ³
	Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 5 of 12

PNEC values

CAS No	Substance	Value
67-64-1	Acetone; Propan-2-one; Propanone	
	Freshwater	10,6 mg/l
	Marine water	1,06 mg/l
	Freshwater sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Soil	29,5 mg/kg
	Freshwater (intermittent releases)	21 mg/l
	Micro-organisms in sewage treatment plants (STP)	100 mg/l

8.2. Exposure controls

Appropriate engineering controls

Do not breathe gas/fumes/vapour/spray. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: goggles. DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. EN ISO 374

Suitable material: Butyl caoutchouc (butyl rubber) (0,5 mm) Breakthrough time (maximum wearing time) < 240 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Usually no personal respirative protection necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	blue	
Odour:	like: Solvent	
pH-Value:		not applicable

Changes in the physical state

Melting point:	not applicable
Initial boiling point and boiling range:	< -20 °C
Flash point:	< -20 °C
Sustaining combustion:	No data available

Flammability

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 6 of 12

Solid: not applicable

Gas: not applicable

Explosive properties

Heating may cause an explosion.

Lower explosion limits: 1,5 vol. %

Upper explosion limits: 10,9 vol. %

Ignition temperature: > 200 °C

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,64 g/cm³

Water solubility:
(at 20 °C) practically insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	Acetone; Propan-2-one; Propanone				
	oral	LD50 5800 mg/kg	Rat	J Toxicol Environ Health 15: 609-621 (19)	Undiluted acetone applied to female rats
	dermal	LD50 > 7426 mg/kg	Rabbit	Toxicol Appl Pharmacol 7: 559-565. (1965)	other: Code of federal regulations: 21 C
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Study report (1988)	Group of rats were exposed to test subst

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Acetone; Propan-2-one; Propanone; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
106-97-8	butane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
67-64-1	Acetone; Propan-2-one; Propanone					
	Acute fish toxicity	LC50 mg/l	8120	96 h	Pimephales promelas	Publication (1984) OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia pulex	Publication (1978) The toxicity of acetone towards daphnids
	Algae toxicity	NOEC	430 mg/l	4 d		
	Crustacea toxicity	NOEC mg/l	2212	28 d	Daphnia magna	Arch Environm Contam Toxicol 12: 305-310 Study conducted comparable to OECD 211 w
	Acute bacteria toxicity	(61150 mg/l)		0,5 h	activated sludge of a predominantly domestic sewage	Water Res 26: 887-892 (1992) ISO 8192
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50	11,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995) OECD Guideline 201
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202

12.2. Persistence and degradability

The product has not been tested.

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 9 of 12

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	Acetone; Propan-2-one; Propanone			
	Biodegradation	91%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	Biodegradation	98%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
74-98-6	propane	1,09
67-64-1	Acetone; Propan-2-one; Propanone	-0,23

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	Acetone; Propan-2-one; Propanone	3		Unpublished calculat

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number:** UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 10 of 12

14.4. Packing group:

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

Transport category:

2

Tunnel restriction code:

D

Inland waterways transport (ADN)

14.1. UN number:

UN 1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2

14.4. Packing group:

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

Marine transport (IMDG)

14.1. UN number:

UN 1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Hazard label:

2.1



Special Provisions:

63, 190, 277, 327, 344, 381, 959

Limited quantity:

1000 mL

Excepted quantity:

E0

EmS:

F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

UN 1950

14.2. UN proper shipping name:

AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Hazard label:

2.1



Special Provisions:

A145 A167 A802

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 11 of 12

Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC):	87,683 % (561,172 g/l)
2004/42/EC (VOC):	87,683 % (561,172 g/l)
Information according to 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC , 2008/47/EC
Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3,4,7,8,9,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

EickSkin Adhaesiv-Spray (952600)

Revision date: 26.08.2020

Page 12 of 12

UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)